

Exterior Sheathing Family

From best-in-class Dens® fiberglass mat gypsum panels to cost-effective paper face sheathing, Georgia-Pacific Gypsum has the right product portfolio to meet your needs *and* code requirements.



Product Comparisons Features/Benefits	½" Regular		⅝" Type X Fire-Rated	
	DensGlass® Sheathing	ToughRock® Sheathing	DensGlass® Fireguard® Sheathing	ToughRock® Fireguard X™ Sheathing
GOLD Fiberglass Mat Provides Mold and Moisture Resistance	✓		✓	
Mold-Resistant Core and Facers (ASTM D3273)	✓		✓	
Higher strengths and stiffness allow for easier handling	✓		✓	
Recycled Paper Face, Back and Long Edges		✓		✓
Code-Compliant Racking Strength (ASTM E72)	✓	✓	✓	✓
Fire-Resistant Classified by UL (ASTM E119)			✓	✓
Combustibility (ASTM E136)	Noncombustible Face & Core	Only Core	Noncombustible Face & Core	Only Core
Installation Over Wood or Metal Studs	✓	✓	✓	✓
High Compressive Strength Provides Durability for Cladding Attachments	✓	✓	✓	✓
Ideal for Use in High-Rise Commercial Structures	✓		✓	
Acceptable for Use in Low-Rise/Mid-Rise Residential and Commercial Structures	✓	✓	✓	✓
Negative Uniform Wind Load Listed	ASTM E330		ASTM E330	
ASTM Compliant	ASTM C1177	ASTM C1396	ASTM C1177	ASTM C1396
Maximum Exposure to Normal Weather Conditions	12 Months*	30 Days**	12 Months	30 Days**

*Limited warranty against delamination and deterioration. For complete warranty details, visit www.gpgypsum.com.
**As defined in GA-253-06.1.

TECHNICAL HOTLINE: 800-225-6119

Sales Information and Order Placement

U.S.A. West: 1-800-824-7503
 Midwest: 1-800-876-4746
 S. Central: 1-800-231-6060
 Southeast: 1-800-327-2344
 Northeast: 1-800-947-4497

CANADA Canada: 1-800-387-6823
 Quebec: 1-800-361-0486



DensGlass®
Sheathing
TOUGHROCK®